



VIVITAR laboratories

**THE SOLUTION<sup>®</sup>**

# **OXYGEN CONCENTRATOR**

PRODUCT CATALOGUE



## Specifications

- Model: OLV-POC4
- Charging: 100V-240V AC / DC 14.6V
- Max Flow: 800ml/min  
(Equivalent to 4L continuous oxygen)
- Oxygen Concentration: 93%±3% (1st-4th gear)
- Dimensions: 19.3\*8.3\*17.3cm  
7.6\*3.27\*6.8in
- Weight: 1.7kg (3.74lb) with battery
- Battery Life: 55 min - 160 min
- Charging Time: Within 2 hours
- Operation Sound: ≤60db



## Effortlessly breathe oxygen, anytime, anywhere.



1.7KGS  
(3.74lbs)



High altitude  
5200m



Multi-alarm  
systems



Modular  
design



Type-C power cord



Nasal Cannula



Bag



Secondary filter



DC power adaptor  
(Optional)

## Specifications

- Flow Range: 0-5L/min (OLV-5S);  
0-10L/min (OLV-10S)
- Oxygen Concentration: 90%-96%
- Maximum Limited Pressure: 100Kpa  
(General Pressure: 20-60Kpa)
- Sound Level : ≤45db (OLV-5S)  
≤55db (OLV-10S)
- Input Power: 500VA (OLV-5S);  
800VA (OLV-10S)
- Time Setting: 30-180min
- Machine Dimensions: 35\*25\*67cm (13.7\*9.8\*26in)
- Warranty: 2 years

## Optional Function

- Nebulizing Rate: 0.15ml/min
- Dual Flow: Two person can use at same time
- Lower Purity Alarm
- Remote Control

## Package

- 1PCS/1Carton
- G.W/N.W: 25/23kg (OLV-5S);  
30/28kg(OLV-10S)
- Carton Size: 43\*38\*75cm
- 20`GP: 234 sets
- 40`GP: 486 sets



24H/7D  
working



90%-96% oxygen  
concentration



Wheels with  
brakes



Optional wire-less  
remote control

## Specifications

- Nebulizer Function: OLV-5AW/OLV-10W
- Maximum Nebulizing Rate:  $\geq 0.15\text{mL/min}$  (OLV-10W)
- Dual Flow: Optional
- Flow Range: 0-5L/min (OLV-5A);  
0-10L/min (OLV-10)
- Oxygen concentration: 90%-96%
- Maximum Limited Pressure: 100Kpa  
(General pressure: 20-60Kpa)
- Sound Level :  $\leq 45\text{db}$  (OLV-5A)  
 $\leq 55\text{db}$  (OLV-10)
- Input Power: 500VA (OLV-5A);  
800VA (OLV-10)
- Machine Dimensions: 34\*30\*56cm (13\*11.8\*22in)
- Warranty: 2 years

## Package

- 1PCS/1Carton
- G.W/N.W: 17/15kg (OLV-5A);  
20/22kg (OLV-10)
- Carton size: 44\*39\*69cm (Single Carton)
- 45\*40\*71cm (Double Cartons)
- 20`GP: 210 sets
- 40`GP: 435 sets



Large LED display



Voice function



90%-96% oxygen concentration



Light weight

## Specifications

- Flow Range: 1-5L/min adjustable
- Oxygen Concentration: 90%±3% (1L)
- Sound Level: Less than 40 db
- Input Power: 105VA
- Machine Weight: 5kg
- Sound Level : ≤40db
- Battery: 10000mA rechargeable (1H after full recharged)
- Three power supply methods: At home by plug in;  
Outside by rechargeable battery; In the car by car inverter

## Package

- 1PC/1Carton
- G.W/N.W: 11/7kg
- Carton size: 34.5\*39\*55cm(with all parts)  
36\*40\*21cm(Single machine)
- 20`GP: 360sets
- 40`GP: 720 sets



Continuous Flow



Ultra-silence




Anion function



Electronic flow meter



Use in Car



Rechargeable battery



Trolley



Portable bag

## Specifications

- Flow Range: 1-5L/min adjustable
- Oxygen Concentration: 90%±3% (1L)
- Sound Level: Less than 40 db
- Input Power: 105VA
- Machine Weight: 5kg
- Sound Level: ≤40db
- Battery: 10000mA rechargeable (1H after full recharged)
- Three Power Supply:
  - At home by plug in
  - Outside by rechargeable battery
  - In the car by car inverter

## Package

- 1 PC/1Carton
- G.W/N.W: 11/7kg
- Carton size: 34\*31\*56cm (with all parts)  
29\*23\*43 cm (Single machine)
- 20`GP: 472sets
- 40`GP: 980 sets



Light weight 5kg



Ultra-silence



Golden / Blue  
optional



Anion function



High/Low oxygen concentration



3 gears adjustable



Simulated altitude 1200m to 7000m



Free OEM

## Specifications

- High Oxygen Delivery Rate: 10L/min
- Hypoxic Delivery Rate: 100L/min
- Maximum Limited Pressure: 100Kpa  
(General pressure: 20-60Kpa)
- Sound level: ≤50db
- Input Powe: 800VA
- Machine Dimensions: 35\*25\*67cm  
(13.7\*9.8\*26in)

## Package

- 1PC/1Carton
- G.W/N.W: 30/28kg
- Carton size: 43\*38\*75cm





Ergonomic  
fit mask



1000L  
oxygen bag



93% oxygen  
concentration



Smart Timer  
Integration

## Specifications

- Flow Range: 0-10L/min
- Oxygen Concentration: 90%-96%
- Maximum Pressure Limit: 138Kpa
- Sound level: ≤55db
- Input Power: 800VA
- Time Setting: 30-180 min
- Machine Size: 35\*25\*67cm  
13.7\*9.8\*26in
- Oxygen Bag Capacity: 1000L
- Oxygen Bag Size: 11.4\*9\*17in
- Material: TPU, Environmentally friendly material, odorless







High pressure  
adjust to 100kpa



OEM service  
available



Customized  
oxygen outlet

## Specifications

- Flow Range: 0-5L/min
- Oxygen Concentration: 90%-96%
- Maximum Limited Pressure: 138Kpa  
(General pressure:20-60Kpa)
- Sound Level: ≤45db
- Input Power: 500VA
- Machine Dimensions: 49\*27\*56cm  
(19\*10.6\*22in)
- Warranty: 2 years

## Package

- 1PC/1Carton
- G.W/N.W: 24/22kg
- Carton size: 56\*33\*65cm
- 20`GP: 204sets
- 40`GP: 559 sets





Continuous flow  
0.5L-20L



Dual Flow



High oxygen  
concentration

## Specifications

- Flow Range: 0-20L/min
- Oxygen Concentration: 90%-96%
- Maximum Limited Pressure: 100Kpa  
(General pressure:20-60Kpa)
- Sound Level : ≤58db
- Input Power: 1600VA
- Machine Dimensions: 94\*40\*84cm (37\*15.7\*33in)
- Maximum Nebulizing Rate: ≥0.15mL/min
- Warranty: 1 year

## Package

- 1PC/1 wooden box
- G.W/N.W: 85/71kg
- Carton size: 94\*45\*86cm
- 20`GP: 60sets
- 40`GP: 120 sets

